

DuPont™ Booster™ LLD -100

Booster™ resins Product Data Sheet

Description

Product Description Booster™ LLD-100 is a modified linear low-density polyethylene polymer intended for use as a melt strength enhancer in extrusion processing of LLDPE and HDPE resins.

Restrictions

Material Status • Commercial: Active

Typical Characteristics

Uses • Plastics Modification

Features Booster™ can significantly increase productivity in the extrusion processing of LLDPE and HDPE resins. Booster™ does not interfere with other additives, and is approved for food contact applications.

Characteristics / Benefits Increases in melt strength achieved by the addition of Booster™ can mean:
 - production rate increases of up to 50%
 - enhanced gauge uniformity, allowing downgauging of up to 20%
 - enhanced capability for producing both very thin and very thick films

Applications * Blown & Cast Film
 * Mono & Multi layer structures
 * Extrusion Coating
 * Blow Molding

Typical Properties

Physical	Nominal Values	Test Method (s)	
Density ()	0.93 g/cm ³	ASTM D792	ISO 1183
Melt Flow Rate (190°C/2.16kg)	75 g/10 min	ASTM D1238	ISO 1133
Thermal	Nominal Values	Test Method (s)	
Melting Point (DSC)	123°C (253°F)	ASTM D3417	ISO 3146

Processing Information

General

Maximum Processing Temperature 300°C (572°F)

General Processing Information Booster™ is supplied in pellet form, and is normally added to the base resin at a level of 1 to 3 wt%, dependent upon the desired level of productivity improvement

In general, when using Booster™, no processing changes are necessary to regular recommended extrusion conditions. Process temperatures must be high enough to produce a melt free from localized temperature fluctuations and shear stresses.

Although lower processing temperatures may give slightly higher melt strength, they can result in poor-quality melt and film with less than optimum physical properties. The addition of Booster™ will more than compensate for any loss of melt strength caused by higher temperatures.

Scrap film containing Booster™ can be reclaimed and reprocessed; gel levels and film physical properties will be comparable to those seen with regular resin reclaim

Note: Booster™ does not reduce melt fracture, nor does it act as a lubricant to reduce extruder power requirements.

FDA Status Information

USA: --- When used in a food-approved grade of LLDPE at a level of 2%, Booster™ complies with Section 177.1520 of Title 21, Code of Federal Regulations, entitled Olefin Polymer.

Regulatory Information

For information on regulatory compliance outside of the U.S., consult your local DuPont representative.

Safety & Handling

As with any hot material, care should be taken to protect the hands and other exposed parts of the body when working with molten polymer.

At elevated temperatures, these resins can evolve low concentrations of fumes. When resins are overheated, more extensive decomposition may occur. Because fumes produced during exposure to high temperatures may be combustible, exposure of overheated resin to atmospheric oxygen should be avoided if possible. Adequate local ventilation should be provided to remove the fumes from the work area.

Disposal of scrap material presents no special problems, and may be accomplished by landfill or by incineration by a properly operated incinerator. Disposal should comply with local, state, and federal regulations. Resin pellets can be a slipping hazard. Loose pellets should be swept up promptly to prevent falls.

For more detailed information on the safe handling and disposal of these resins, a Product Safety Bulletin and OSHA Material Safety Data Sheets can be obtained from the Regional Office serving you.

Read and Understand the Material Safety Data Sheet (MSDS) before using this product

Regional Centres

DuPont operates in more than 70 countries. For help finding a local representative, please contact one of the following regional customer contact centers:

Americas

DuPont Company, BMP26-2363
Lancaster Pike & Route 141
Wilmington, DE 19805 U.S.A.
Telephone +1 302-774-1161
Toll-free (USA) 800-628-6208
Fax +1 302-999-4399

DuPont do Brasil, S.A.
Alameda Itapecuru, 506
06454-080 Barueri, SP Brasil
Telephone +55 11 4166 8122
Fax +55 11 4166 8720

Asia Pacific

DuPont China Holding Co., Ltd.
Shanghai Branch
399 Keyuan Road, Bldg. 11
Zhangjiang Hi-Tech Park
Pudong New District, Shanghai
P.R. China (Postcode: 201203)
Telephone +86 21 3862 2888
Fax +86-21-3862-2889

Europe / Middle East / Africa

DuPont de Nemours Int'l. S.A.
2, Chemin du Pavillon Box 50
CH-1218 Le Grand Saconnex
Geneva, Switzerland
Telephone +41 22 717 51 11
Fax +41 22 717 55 00

fusabond.dupont.com

The data listed here fall within the normal range of properties, but they should not be used to establish specification limits nor used alone as the basis of design. The DuPont Company assumes no obligations or liability for any advice furnished or for any results obtained with respect to this information. All such advice is given and accepted at the buyer's risk. The disclosure of information herein is not a licence to operate under, or a recommendation to infringe, any

CAUTION: Do not use DuPont materials in medical applications involving implantations in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of DuPont POLICY Regarding Medical

patent of DuPont or others. Since DuPont cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information.

Applications H-50103-3 and DuPont CAUTION Regarding Medical Applications H-50102-3.

Copyright © 2009 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, and trademarks designated with "®" are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

This data sheet is effective as of 09/14/2007 05:15:04 PM and supersedes all previous versions.