

# DuPont™ Krytox®

PRODUCTS FOR THE POWER GENERATION INDUSTRY

DUPONT PERFORMANCE LUBRICANTS PROVIDES THE SOLUTION YOU NEED

Application	DuPont™ Krytox® Product	Temperature Range (°F)	Temperature Range (°C)	ISO Viscosity	Properties
<b>Coal Fired Power Plant</b>					
Steam Turbine Governor	TG	-4 to 610	-20 to 320	500	High performance, extreme pressure and extreme high temperature anti-fretting grease.
Sootblower Carriage Bearings and Gears	SB	-40 to 535	-40 to 280	100-500	High temperature non-oxidizing grease designed to extend bearing, gear and seal life.
Turbine Pedestal Thrust Bearing	Contact DuPont Representative	-22 to 625	-30 to 330	440-740	Very high temperature grease. Safe around all chemicals. Won't wash out with water or solvents.
Hydro Grate Stoker	XHT-ACX	14 to 572	-10 to 300	680	Very high temperature grease. Safe around all chemicals. Won't wash out with water or solvents.
Damper Bearings	GPL 227	-22 to 550	-30 to 288	460	High temperature, long life, high load carrying, anti-corrosion grease.
Valves (Steam and other high temperature)	GPL 207	-22 to 550	-30 to 288	460	High temperature, long life grease.
Knife Gate Valves	Contact DuPont Representative	-22 to 572	-30 to 300	460-500	High temperature, long life grease.
Fan Bearings	GPL 226	-33 to 500	-36 to 260	Varies based upon specific application details	High temperature, long life, high load carrying, anti-corrosion grease.
<b>Natural Gas Fired Power Plant</b>					
Gas Turbine Trunion Bearing	XHT-BDZ	23 to 750	-5 to 399	1000	Extreme high temperature grease.
<b>Nuclear Power Plant</b>					
Steam Turbine Governor	TG	-4 to 610	-20 to 320	460	High performance, extreme pressure and extreme high temperature anti-fretting grease.
Fan Bearings	GPL 226	-33 to 500	-36 to 260	220	High temperature, long life, high load carrying, anti-corrosion grease.
Radiation Resistant Lubricant	EG 2000	-33 to 500	-36 to 260	220	High temperature, long life, low volatility grease.
<b>General MRO Applications</b>					
Switchgear electrical contact grease	EG 3000	-22 to 550	-30 to 288	460	High temperature, long life, low volatility grease.

**This is intended for information only. To ensure selection of the best product for your application, please contact your sales representative at 1-800-424-7502.**

Copyright © 2006 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and Krytox® are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.

K-16091 (8/06) Printed in the U.S.A.

The information set forth herein is furnished free of charge and based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.



The miracles of science™