

# DuPont™ Krytox®

## PRODUCTS FOR THE AUTOMOTIVE INDUSTRY

DUPONT PERFORMANCE LUBRICANTS PROVIDES THE SOLUTIONS YOU NEED

Proven Applications	Part	DuPont™ Krytox® Grade	Temperature Range, °C	Base Oil ISO Viscosity Range	Value Krytox® Brings
Fan Clutch	Bearing	GPL 224, 225, AUT 2245	-50 to +200	60 to 160	High Temperature Stability, Very Long Life, Resistance to Underhood Contaminates
Clutch Pilot Bearing	Bearing	GPL 295	-40 to +200	160	Fretting Corrosion Resistance, High Temperature Stability, Very Long Life
Battery Vent	Sliding Vent	GPL 106	-40 to +200	240	Resistance to Acidic Decomposition, Elimination of Stick-Slip
Exterior Rearview Mirror	Plastic Gear	GPL 204	-50 to +180	60	Superior Lubrication, Very Long Life
Spark Plug Boots		AUT 523, GPL 204, 205	-50 to +200	60 to 160	Elimination of Boot-Plug Adhesion, Elimination of Boot Cracking, Very Long Life
Cooling Fan	Sintered Bearings	GPL 105	-40 to +200	160	High Temperature Stability, Very Long Life
Alternator	Rear Bearing	GPL 224, 225, AUT 2245	-50 to +200	60 to 160	High Temperature Stability, Very Long Life, Resistance to Underhood Contaminates
Cooling System Thermostat	Actuator Rod	GPL 207	-30 to +200	440	Resistance to Coolant Wash-Off, Very Long Life
O-ring Lubrication/Assembly Lube	Elastomeric Seals, Miscellaneous Parts	GPL 205	-40 to +200	160	Broad Material Compatability, High Temperature Stability, Very Long Life
NVH (Squeak Elimination)	Interior Parts, Window Seals	GPL 103, 104, 105 GPL 203, 204, 205	-50 to +200	30 to 160	Broad Material Compatability, Non-Staining, Very Long Life, Elimination of Stick-Slip
Hydraulic Clutch Actuator Lubricant	Clutch Hydraulic Master/Slave Cylinder Lubricant	GPL 205	-40 to +200	160	Broad Material Compatability, Very Long Life, Elimination of Stick-Slip
Engine/Turbo Cooling System	Fittings	GPL 105	-40 to +200	160	Assembly Aid, Compatibility with Materials and Coolants

**Custom Solutions — Let us work with you to solve your toughest reliability challenges.**

Custom Application	Part	DuPont™ Krytox® Grade	Temperature Range, °C	Base Oil ISO Viscosity Range	Value Krytox® Brings
Heavy Duty Truck Automatic Clutch	Bearings	XP 2C5	-40 to +170	160	Long Life, High Temperature Stability, Resistance to Separation Under Centrifugal Load
EGR Valve	Actuator Gears	XP 2C5	-40 to +170	160	Long Life, High Temperature Stability, Resistance to Diesel Exhaust Fumes
Windshield Wiper Motor	Bushing	GPL 103		30	Long Life, High Temperature Stability
Electronic Parking Brake Mechanism	Various	GPL 103	-40 to +150	30	Long Life, High Temperature Stability, Consistent Response/Torque Over Temperature Range



*The miracles of science™*

**This is intended for information only. To ensure selection of the best product for your application, please contact your sales representative at 1-800-424-7502.**

**United States** (800) 424-7502

E-mail: krytox@usa.dupont.com

**Canada** (800) 387-2122

E-mail: products@can.dupont.com

**Europe, Mideast, and Africa** +41 22 717 5086

E-mail: lubricants@lux.dupont.com

**Asia/Pacific**—Including India—(65) 6586 3073

E-mail: krytox.lubricants@sgp.dupont.com

**Mexico and Central America** +011 52 55 5722 1150

E-mail: ceac@mex.dupont.com

**South America**—All Countries—55 11 4166 8601

E-mail: produtos.brasil@bra.dupont.com

**[www.krytox.com](http://www.krytox.com)**

*Copyright © 2008 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™ and Krytox® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.*

*K-17456-1 (01/08) Printed in the U.S.A.*

The information set forth herein is furnished free of charge and based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.



*The miracles of science™*