

DuPont™ Cyrel® 2000 EC/LF

STATE-OF-THE-ART EXPOSURE, LIGHT FINISHER AND POST-EXPOSURE UNIT.

DuPont Packaging Graphics

To help our customers gain competitive advantage in the global packaging graphics value chain.

DuPont Packaging Graphics continues to be a global technology leader in supplying flexographic printing systems. Our scientists continue to develop unique solutions based on new technologies to help our customers expand their business by taking advantage of new profitable packaging printing opportunities. DuPont Packaging Graphics portfolio of products includes Cyrel® brand photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.

The Cyrel® 2000 EC/LF is the state-of-the-art exposure, light finisher and post-exposure unit, designed to expose all Cyrel® photopolymer plates, including Cyrel® FAST.

The exposure bed can accommodate a plate up to 42 inch by 60 inch (1,067 mm by 1,524 mm). The exposure portion is an automated "clamshell" design for optimum productivity and excellent exposure and vacuum draw down.

Designed with customer needs in mind, it is easy to install, support, maintain, and operate. It is robust, cost-effective and extremely reliable.

The exposure section is made of a swiveling top holding thirty-eight UV-A fluorescent tubes with built-in reflectors.



DuPont™ Cyrel® 2000 EC/LF

One yellow control tube illuminates the exposure bed while inspecting the plate surface. The lower part features a water-cooled bed.

Unique to this exposure unit is the water-cooled, closed loop system that controls the exposure bed temperature, producing a more even polymerization of the plate, which translates into predictable and consistent exposures. The Cyrel® 2000 EC/LF has been equipped with an integrator that compensates for the decrease in light output as the bulbs age. This integration scheme allows for consistent exposure of the plates over the life of the bulbs.

To meet the demanding needs of high quality photopolymer plates the user can, easily customize the 20 basic exposure set-ups.

The post exposure and light finisher section is located in the top drawer below the exposure section. The drawer

is mounted on ball-slides and holds twenty-six UV-C tubes and twenty-seven UV-A tubes. The computer control board allows the user to perform post exposure and finishing in the preferred sequence, or simultaneously. The post exposure and finisher section has 20 basic set-ups that can be easily customized by the user.

Special features are available with the equipment. Each tube is constantly monitored by a photo-sensor. If the light emission of one or more tubes decreases below a set point, the user is alerted. This detection system is particularly useful and therefore enhances the SAFE use of the equipment under the most difficult conditions.

To assist the user in maintaining the highest level of efficiency, three counters are imbedded in the computer control board to keep track of the number of hours the UV-A and UV-C tubes have been working.



The miracles of science™

DuPont Packaging Graphics

“Advancing Flexography”

General	Details	Other notes
Equipment Name	DuPont™ Cyrel® 2000 EC/LF	Combined unit
SAP Article Number	MH89533	Cooled exposure, dryer, post exposure and light finisher
Packing	Crate	
Max. nominal plate width	42 inch – 1,067 mm	
Max. nominal plate length	60 inch – 1,524 mm	
UV-A tubes wave length	360-380 nm	
UV-C tubes wave length	254 nm	
Electrical (field configurable)	210/240 Volt – 50/60hz * 370/420 Volt – 50/60hz **	Three phases and ground Three phases, neutral and ground
Power (nominal)	9.5 kW	
Current (nominal load)	27 Amp @ 230 V * 16 Amp @ 400 V **	Connection wires 4 x 10 mm ² * Connection wires 5 x 10 mm ² **
Grounding	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
Exhaust (Light Finisher)	Ø 5.5 inch – 140 mm	1,000 m ³ /h – 590 scfm (min)
Environmental Data	Temperature range 65° to 85° F – 8.3° C to 29.4° C	Relative humidity from 20% to 85% non-condensing
Dimension	L 104 inch – 2,600 mm W 68 inch – 1,700 mm H 43 inch – 1,100 mm	104 inch – 2,600 mm 68 inch – 1,700 mm 94 inch – 2,400 mm (open)
Colour	Grey and Red	DuPont grey and DuPont red

* Electrical configuration 1 ** Electrical configuration 2

All technical information set out herein is provided free of charge and is based on technical data, which DuPont believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.

Du Pont de Nemours (Deutschland) GmbH
DuPont Imaging Technologies
Hugenottenallee 173
D-63257 Neu Isenburg
Deutschland
Telefon: +49 (0) 61 02 184400

Du Pont Imaging Technologies
DuPont (U.K.) Limited
DuPont Imaging Technologies
Wedgwood Way, Stevenage
Hertfordshire SG1 4QN
Tel. +44 (0)1438 734863

To learn more, visit www.cyrel.dupont.com
or contact your Cyrel® specialist



The miracles of science™