



# DuPont™ Cyrel® 3000 LF

## State-of-the-Art Light Finisher




DuPont™ Cyrel® 3000 LF

DuPont Packaging Graphics continues to be a global technology leader in the development and supply of flexographic printing systems. Our R&D team continues to develop innovative new solutions to help our customers expand their business by taking advantage of new and profitable opportunities in the growing flexographic packaging market. The DuPont Packaging Graphics portfolio of products includes DuPont™ Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.

DuPont™ Cyrel® Systems: Higher quality at high speed.

**The DuPont™ Cyrel® 3000 LF is designed with customer needs in mind; it is easy to install, support, maintain and operate. It is robust, extremely cost effective and reliable.**



Floor Plan

### Benefits

- Maximum plate size 1,320 x 2,030 mm (52" x 80")
- Excellent post expose and light finishing
- Stand alone configuration
- Simple to install
- Robust and easy to support
- Optimum productivity

### Product Features

DuPont™ Cyrel® 3000 LF is capable of post exposing and light finishing high quality photopolymer plates up to a maximum format of 1,320 x 2,030 mm (52" x 80"). This post exposure and light finisher module can be installed as a stand alone unit or may be combined with a Cyrel® 3000 D dryer.

The light finisher contains 30 UV-C tubes and 31 UV-A tubes. The control panel is fitted with an electronic timer and hour counter. The control panel allows the user to perform post exposure and finishing in the preferred sequence or simultaneously.

The Cyrel® 3000 LF is delivered in one piece.



Download latest version



# DuPont™ Cyrel® 3000 LF

## State-of-the-Art Light Finisher

Technical Data		
General	Details	Other Notes
<b>Equipment Name</b>	DuPont™ Cyrel® 3000 LF	Light Finisher (Stand not included)
<b>SAP Article Number</b>	M154334	
<b>Plate Thickness</b>	0.5 mm to 7.0 mm	0.019" to 0.27"
<b>Max. Nominal Plate Width</b>	1,320 mm (52")	
<b>Max. Nominal Plate Length</b>	2,030 mm (80")	
<b>UV-A Tubes Wave Length</b>	360 nm – 380 nm	31 tubes
<b>UV-C Tubes Wave Length</b>	254 nm	30 tubes
<b>Electrical (Field Configurable)</b>	400 Volt – 50 / 60 hz (+10%–5%) 230 Volt – 50 / 60 hz (+10%–5%)	3Ph / N / PE 3Ph / PE
<b>Power (Nominal)</b>	5.6 kW	
<b>Current (Nominal Load)</b>	8 Amp @ 400 Volt 17 Amp @ 230 Volt	
<b>Connecting Wires</b>	400 Volt configuration 230 Volt configuration	5 x 4 mm <sup>2</sup> 5 x 4 mm <sup>2</sup>
<b>Grounding</b>	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
<b>Exhaust</b>	Ø 120 mm (4.72")	2 x 1290 m <sup>3</sup> / 759 cfm
<b>Environmental Data</b>	Temperature range: 15°C to 30°C (59°F to 86°F)	Relative humidity from 40% to 60% non-condensing
<b>Compressed Air Supply</b>	NA	NA
<b>Dimensions</b>	<b>Uncrated</b>	<b>Crated</b>
<b>D</b>	2,000 mm (78.73")	2,310 mm (90.94")
<b>W</b>	2,900 mm (114.17")	3,060 mm (120.47")
<b>H</b>	300 mm (11.81")	600 mm (23.62")
<b>Weight</b>	380 kg (837 lbs)	600 kg (1,323 lbs)
<b>Colour</b>	DuPont Grey & DuPont Red	

For more information on DuPont™ Cyrel® or other DuPont Packaging Graphics products, please contact your local representative:

DuPont de Nemours (Deutschland) GmbH  
DuPont Electronics & Communications  
Hugenottenallee 173 – 175  
63263 Neu-Isenburg  
Germany  
Tel: +49 (0) 6102 18 4400

DuPont (U.K.) Limited  
DuPont Electronics & Communications  
Wedgwood Way, Stevenage  
Hertfordshire SG1 4QN  
United Kingdom  
Tel: +44 (0) 1438 73 4863

[www.cyrel.eu](http://www.cyrel.eu)

© 2012 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™ and Cyrel® are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates. All technical information set out herein is provided free of charge and is based on technical data, which DuPont believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.