

# DuPont™ Cyrel® 1000 EC/LF

STATE-OF-THE-ART EXPOSURE, LIGHT FINISHER AND POST-EXPOSURE UNIT

## DuPont Packaging Graphics

**To help our customers gain competitive advantage in the global packaging graphics value chain.**

DuPont Packaging Graphics continues to build upon its position as the leading global supplier of flexographic printing systems. Our scientists continue to develop unique solutions based on new technologies to help our customers expand their business by taking advantage of new profitable packaging printing opportunities.

The portfolio of products includes Cyrel® brand photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel®FAST thermal system.

**The Cyrel® 1000 EC/LF is the state-of-the-art exposure, light finisher and post-exposure unit, designed to expose all Cyrel® photopolymer plates, including Cyrel®FAST.**

The exposure bed can accommodate a plate up to 35.4 inch by 47.2 inch. The exposure portion is a “clamshell” design for optimum productivity and excellent exposure and vacuum draw down.

Designed with customer needs in mind, it is easy to install, support, maintain, and operate. It is robust, cost-effective and extremely reliable.

The exposure section is made of a swiveling top holding twenty-four UV-A fluorescent tubes with built-in reflectors. One yellow



### DuPont™ Cyrel® 1000 EC/LF

low control tube illuminates the exposure bed while inspecting the plate surface. The lower part features a water-cooled bed.

Unique to this exposure unit is the water-cooled, closed loop system that controls the exposure bed temperature, producing a more even polymerization of the plate, which translates into predictable and consistent exposures. The Cyrel® 1000 EC/LF has been equipped with an integrator that compensates for the decrease in light output as the bulbs age. This integration scheme allows for consistent exposure of the plates over the life of the bulbs.

To meet the demanding needs of high quality photopolymer plates the user can easily customize the 20 basic exposure set-ups.

The post exposure and light finisher section is located in the top drawer below the exposure section. The drawer is mounted on ball-slides and holds nineteen UV-C tubes and twenty UV-A tubes. The com-

puter control board allows the user to perform post exposure and finishing in the preferred sequence, or simultaneously. The post exposure and finisher section has 20 basic set-ups that can be easily customized by the user.

Special features are available with the equipment. Each tube is constantly monitored by a photo-sensor. If the light emission of one or more tubes decreases below a set point, the user is alerted. This detection system is particularly useful and enhances the SAFE use of the equipment under the most difficult conditions.

To assist the user in maintaining the highest level of efficiency, three counters are imbedded in the computer control board to keep track of the number of hours the UV-A and UV-C tubes have been working.

Located beneath the finisher are three drawers for convenient storing of Cyrel® plates, films and supplies.



*The miracles of science™*

**DuPont Packaging Graphics**  
**“Advancing Flexography”**

General	Details	Other notes
<b>Equipment Name</b>	DuPont™ Cyrel® 1000 EC/LF	Combined unit
<b>Global material code</b>	MH74451A	Cooled exposure, post exposure and light finisher
<b>Packing</b>	Crate	
<b>Max. nominal plate width</b>	36 inch	
<b>Max. nominal plate length</b>	48 inch	
<b>UV-A tubes wave length</b>	360 nm	
<b>UV-C tubes wave length</b>	254 nm	
<b>Electrical (field configurable)</b>	208/250 Volt – 50/60hz * 370/440 Volt – 50/60hz **	Three phases and ground * Three phases, neutral and ground **
<b>Power (nominal)</b>	5 kW	Connection wires 5 x 2.5 mm <sup>2</sup>
<b>Current (nominal load)</b>	25 Amp * 20 Amp **	
<b>Grounding</b>	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
<b>Exhaust (Light Finisher)</b>	Ø 5.5 inch (Connection)	590 scfm
<b>Environmental Data</b>	Temperature range 65° to 85° F – 8.3° C to 29.4° C	Relative humidity from 20% to 85% non-condensing
<b>Dimension</b>	L W H	59 inch 71 inch 43 inch
<b>Net weight</b>	1,069 lb.	
<b>Dimension w/crate</b>	L W H	65 inch 75 inch 59 inch
<b>Weight w/crate</b>	1,410 lb.	
<b>Color</b>	Grey and Red	DuPont grey and DuPont red

\* Electrical configuration 1    \*\* Electrical configuration 2

*All technical information set out herein is provided free of charge and is based on technical data, which DuPont believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.*

### United States

DuPont Customer Technology Center  
Chestnut Run Plaza, Bldg. 702  
Wilmington, DE 19880-0702  
800.345.9999

### Canada

DuPont Packaging Graphics  
P.O. Box 2200, Streetsville  
Mississauga, Ontario Canada, L5M 2H3  
905.821.5042

To learn more, visit [www.cyrel.dupont.com](http://www.cyrel.dupont.com)  
or contact your Cyrel® specialist



*The miracles of science™*