

# DuPont™ Suva® refrigerants

## Properties and Applications of DuPont R-507 Refrigerant

DuPont R-507 is a non-ozone depleting replacement for R-502 in refrigeration applications. This document will discuss general properties of DuPont R-507 and how it may be used in refrigeration applications.

### Properties

DuPont R-507 is a mixture of hydrofluorocarbon refrigerants HFC-125 and HFC-143a. It is an azeotrope, nonflammable, and has no ozone depletion potential. These properties make it a candidate refrigerant for applications where safety and consistency of performance are needed.

DuPont R-507 will maintain a very consistent composition if leakage occurs in a refrigeration system, which means that operating performance will remain consistent following leakage/recharge cycles. As with all mixtures, we recommend that the liquid phase be removed from the storage cylinder to minimize composition changes when charging. DuPont R-507 should not be mixed with any other refrigerant when charging, recycling, recovering or reclaiming.

**Table 1**  
**General Properties of DuPont R-507**

Boiling Point (1 atm), °C (°F)	-46.7 (-52.1)
Critical Temperature, °C (°F)	70.9 (159.6)
Critical Pressure, kPa (psia)	3793.6 (550)
Latent Heat of Vaporization at Boiling Point, kJ/kg (Btu/lb)	200.5 (86.2)
Saturated Vapor Density at -15°C, kg/cu m (lb/cu ft)	19.6 (1.23)
Ozone Depletion Potential	0
Global Warming Potential	3900
DuPont AEL*, ppm (8 and 12-hour T.W.A.)	1000
Flammability	None

\* AEL (Acceptable Exposure Limit) is an airborne exposure limit established by DuPont toxicologists to which nearly all workers can be repeatedly exposed during a 40-hour workweek, or 8-hour day, without adverse effects. This limit for R-507 is calculated based on the AEL for its individual components.

Being nonflammable, DuPont R-507 can be safely used in commercial systems such as supermarkets or transport refrigeration, where personnel and the public are in the vicinity of the refrigeration equipment. DuPont recommends the use of polyolester

lubricants with DuPont R-507; however, the compressor manufacturer should always be consulted for specific lubricant selection. R-507/polyolester mixtures have better miscibility than R-502/mineral oil at low temperatures, which should aid in oil return for low-temperature applications.

### Operating Characteristics

DuPont R-507 is a long-term replacement for R-502 and offers good operating characteristics when compared to R-502. Capacity and efficiency values should be nearly equivalent to R-502. The compressor discharge temperature may be as much as 7.4°C (13.3°F) lower than with R-502, which may equate to longer compressor life and better lubricant stability. For example, if a system were operated at -17.8°C (0°F) evaporation and 32.2°C (90°F) condensing, with an 18.3°C (65°F) suction gas temperature, estimated values of performance (with R-502 equal to 1.0) are as follows.

**Table 2**  
**Estimated Values of Performance**

Capacity	1.06
Theoretical Efficiency	0.94
Discharge Temperature	7.7°C (13.9°F) lower than R-502
Discharge Pressure	149.9 kPa (21.7 psi) higher than R-502
Suction Pressure	26.8 kPa (3.88 psi) higher than R-502

### Commercial Availability

DuPont R-507 components are TSCA (U.S.A.) and EINECS (Europe) listed; also, DuPont R-507 has been recognized by Underwriters Laboratories (UL).

Commercial quantities of DuPont R-507 are available. Contact DuPont at locations shown on the back page, or contact any DuPont authorized distributor for more information.



*The miracles of science™*

---

## For Further Information:

DuPont Fluorochemicals  
Wilmington, DE 19880-0711  
(800)235-SUVA  
[www.suva.dupont.com](http://www.suva.dupont.com)

---

### Europe

DuPont de Nemours  
International S.A.  
2 Chemin du Pavillon  
P.O. Box 50  
CH-1218 Le Grand-Saconnex  
Geneva, Switzerland  
41-22-717-5111

### Canada

DuPont Canada, Inc.  
P.O. Box 2200, Streetsville  
Mississauga, Ontario  
Canada  
L5M 2H3  
(905) 821-3300

### Mexico

DuPont, S.A. de C.V.  
Homero 206  
Col. Chapultepec Morales  
C.P. 11570 Mexico, D.F.  
52-5-722-1100

### South America

DuPont do Brasil S.A.  
Alameda Itapecuru, 506  
Alphaville 06454-080 Barueri  
São Paulo, Brazil  
55-11-7266-8263

DuPont Argentina S.A.  
Casilla Correo 1888  
Correo Central  
1000 Buenos Aires, Argentina  
54-1-311-8167

### Pacific

DuPont Australia  
P.O. Box 930  
North Sydney, NSW 2060  
Australia  
61-2-99236111

### Japan

Mitsui DuPont Fluorochemicals  
Co., Ltd.  
Chiyoda Honsha Bldg.  
5-18, 1-Chome Sarugakucho  
Chiyoda-Ku, Tokyo 101-0064 Japan  
81-3-5281-5805

### Asia

DuPont Taiwan  
P.O. Box 81-777  
Taipei, Taiwan  
886-2-514-4400

DuPont China Limited  
P.O. Box TST 98851  
1122 New World Office Bldg.  
(East Wing)  
Tsim Sha Tsui  
Kowloon, Hong Kong  
Phone: 852-734-5398  
Fax: 852-236-83516

DuPont Thailand Ltd.  
9-11 Floor, Yada Bldg.  
56 Silom Road  
Suriyawongse, Bankrak  
Bangkok 10500  
Phone: 66-2-238-0026  
Fax: 66-2-238-4396

DuPont China Ltd.  
Rm. 1704, Union Bldg.  
100 Yenan Rd. East  
Shanghai, PR China 200 002  
Phone: 86-21-328-3738  
Telex: 33448 DCLSH CN  
Fax: 86-21-320-2304

DuPont Far East Inc.  
6th Floor Bangunan Samudra  
No. 1 JLN. Kontraktor U1/14, SEK U1  
Hicom-Glenmarie Industrial Park  
40150 Shah Alam, Selangor Malaysia  
Phone 60-3-517-2534

DuPont Korea Inc.  
4/5th Floor, Asia Tower  
#726, Yeoksam-dong, Kangnam-ku  
Seoul, 135-082, Korea  
82-2-721-5114

DuPont Singapore Pte. Ltd.  
1 Maritime Square #07 01  
World Trade Centre  
Singapore 0409  
65-273-2244

DuPont Far East, Philippines  
8th Floor, Solid Bank Bldg.  
777 Paseo de Roxas  
Makati, Metro Manila  
Philippines  
Phone: 63-2-818-9911  
Fax: 63-2-818-9659

DuPont Far East Inc.  
7A Murray's Gate Road  
Alwarpet  
Madras, 600 018, India  
91-44-454-029

DuPont Far East Inc.—Pakistan  
9 Khayaban-E-Shaheen  
Defence Phase 5  
Karachi, Pakistan  
92-21-533-350

DuPont Far East Inc.  
P.O. Box 2553/Jkt  
Jakarta 10001, Indonesia  
62-21-517-800

---

The information contained herein is based on technical data and tests which we believe to be reliable and is intended for use by persons having technical skill, at their own discretion and risk. Because conditions of use are outside of DuPont control, we can assume no liability for results obtained or damages incurred through the application of the data presented.

Copyright © 2005 DuPont or its affiliates. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and Suva® are registered trademarks or trademarks of DuPont or its affiliates.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF DUPONT.



*The miracles of science™*