

# DuPont™ StoneTech® Professional Advanced Grout Sealer

## TECHNICAL DATA SHEET



### PRODUCT BENEFITS

- Keeps grout looking new
- Apply as soon as two hours after grouting
- Sprayer designed for use on floors and walls
- Maximum protection against most stains
- For natural stone, ceramic and porcelain tile

### RECOMMENDED SURFACES

Grout for natural stone, ceramic and porcelain tile.

### AVAILABLE SIZES

13.5 oz Aerosol Can

### COVERAGE

200–500 linear ft, depending on porosity of surface.

### EXPECTED WEAR

3–5 years on interior surfaces and  
1–3 years on exterior surfaces.

### TECHNICAL INFORMATION

Form:	Aerosol
HMIS Rating:	2,4,0
Flash Point:	<0°F

### VOC CONTENT

PWMIR <1.50 g O<sub>2</sub>/g product  
(Clear Coatings)

### DIRECTIONS

Read entire label before using. Use only as directed. Ensure area is well-ventilated during application and until surface is dry. Open windows and doors and use exhaust fans. Keep children and pets out of area until foot traffic can be resumed. Always test in a small inconspicuous area to determine appropriate application method and desired results. Avoid spraying surfaces not intended for treatment. For new installations, product can be applied as soon as 2 hours after grouting. For best results, wait 4 hours or more. Grout should be firm to the touch before application. For cured installations, grout must be clean, dry, and free of sealers and coatings.

1. Shake well before using
2. Hold can with extended arm 10 to 16 inches from the grout surface, aim nozzle, and spray sealer evenly along the grout line. Keep can tilted to assure even product distribution.
3. After 10 to 15 minutes, wipe entire surface with dry cloth to remove excess sealer. If using on newly applied grout, wipe lightly to avoid disturbing grout.
4. A second coat is recommended and may be applied within one hour of initial application.
5. Dried residue from excess sealer can be removed from tile surfaces by wiping with a dry cloth.
6. On cured grout, surface traffic may begin 2 hours after final application. For newly installed grout, follow manufacturer's guidance. Keep installation dry for a minimum of 12 hours, optimally 36 to 72 hours.

### EMERGENCY/FIRST AID PROCEDURES

**Ingestion:** Do not induce vomiting. Call poison control center. Call a physician immediately.

**Eye Contact:** Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician if eye irritation persists.

**Skin Contact:** Wash skin with mild soap and water. Call a physician if skin irritation persists. Launder affected clothing before re-wearing.

**Inhalation:** Remove to fresh air immediately. Call a physician if respiratory irritation, nausea, or dizziness persists.

### STORAGE AND HANDLING INSTRUCTIONS

**DANGER! EXTREMELY FLAMMABLE.** Contains petroleum distillates (aliphatic hydrocarbons, 68551-16-6), and propane (74-98-6) and butane (106-97-8) as propellants. Do not use near sources of ignition, heat, flame, spark, or live electrical equipment, or while smoking. Vapors can travel to distant ignition sources. VAPOR HARMFUL. Do not breathe vapors or spray mist. USE ONLY IN A WELL-VENTILATED AREA. If unsure whether area is well-ventilated, use NIOSH-approved respirator with a combination HEPA/organic vapor cartridge. Prevent build-up of vapors by opening windows and doors and by using exhaust fans. Intentional misuse by deliberately inhaling contents of this container may be HARMFUL OR FATAL. HARMFUL OR FATAL IF SWALLOWED. Do not ingest. MAY CAUSE EYE, SKIN, AND RESPIRATORY IRRITATION. Avoid eye and skin contact. For safest application, wear protective eyewear, gloves, long sleeves, and long pants. CONTENTS UNDER PRESSURE. Do not puncture, incinerate, or store above 120°F/49°C. Exposure to heat or prolonged exposure to sunlight may cause bursting. Do not discard can in trash compactor or burn. Do not mix product with other chemicals. Rags, clothing, and other equipment wet with product may be combustible. Clean up promptly after job is complete. Remove any clothing that comes in contact with product. Allow rags and clothing to dry in well-ventilated area away from children and pets. When dry, dispose of rags. Wash affected clothing before re-wearing. KEEP OUT OF THE REACH OF CHILDREN. For professional or frequent use, a NIOSH-approved respirator with a HEPA/organic vapor cartridge is recommended. Consult product MSDS.

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements and is packaged in containers with at least 25% post-consumer recycled material.

DuPont StoneTech® Professional  
370 North Wiget Lane, Suite 200  
Walnut Creek, CA 94598

1-877-STONETECH (786-6383)

www.stonetechpro.dupont.com



The miracles of science™

*The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.*

*Copyright © 2008 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, and StoneTech® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.*

K-20507 (08/08)