

DuPont™ StoneTech® Professional Heavy Duty Coating Stripper

TECHNICAL DATA SHEET



PRODUCT BENEFITS

- Professional strength formula
- Removes tough coatings, lacquers, varnishes and epoxy grout haze
- Low odor and non-flammable
- Easy to use, water-based formula

RECOMMENDED SURFACES

Suitable for all natural stone surfaces including slate, marble, and saltillo. Not intended for use on surfaces other than stone and masonry.

AVAILABLE SIZES

Quart, Gallon, 5 Gallon

COVERAGE

80–200 sq ft per gallon, depending on thickness of the application or the amount of coating to be removed.

TECHNICAL INFORMATION

Form:	Viscous Liquid
Specific Gravity:	1.1
HMS Rating:	1,1,0
Flash Point:	>200°F
Freeze Point:	32°F
pH:	7

DuPont StoneTech® Professional
370 North Wiget Lane, Suite 200
Walnut Creek, CA 94598

1-877-STONETECH (786-6383)

www.stonetechpro.dupont.com

DIRECTIONS

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Be sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area until foot traffic resumes. Avoid contact with surfaces not intended to be treated. Product can cause plastics (e.g., PET) to haze, and can dull linoleum surfaces. Avoid applying in direct sunlight. Should not be used in extreme temperatures. Recommended application temperature range is 50°F to 90°F.

1. SHAKE WELL BEFORE USING.
Do not dilute before applying.
2. Wear rubber gloves and eye protection during handling and application to prevent skin and eye contact.
3. Liberally apply an even coat over the required area with a paint brush, mop or paint pad. DO NOT APPLY PRODUCT WITH A SPRAYER. Apply a second coat 10 minutes after the first coat to even out the thickness of the application. Immediately remove product from unintended surfaces with a wet cloth to prevent potential damage to those surfaces.
4. Application times will vary depending on type of coating being removed. The following are approximate application times:
 - Sealer, wax and varnish: 30 to 60 minutes
 - Polyurethane and acrylic: 1 to 2 hours
 - Epoxy grout haze: 1 to 2 hours
5. Do not let Heavy Duty Coating Stripper dry on the surface. If product starts to dry, add water to keep surface wet.
6. Agitate surface with a nylon scrub brush or pad after testing a small area first to make sure that brush or pad will not scratch stone. Surface can be wet with water to enable easier removal of coating.
7. Wipe up residual coating with clean, dry cloths.
8. Rinse surface well with clean water.
9. More than one application may be required; repeat steps 3 through 8 when necessary.
10. Surface traffic may begin 2 hours after removal of coating.

STORAGE AND HANDLING INSTRUCTIONS

CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Do not ingest. Avoid prolonged exposure to vapors. Use in a well-ventilated area. Prolonged exposure by inhalation or skin contact may cause temporary blurring of vision. Rubber gloves and eye protection should be worn during handling and application to prevent skin and eye contact. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 100°F/38°C. Do not mix with other chemicals. Do not flush unused product to surface water or sanitary sewer system. Dispose of in accordance with waste disposal regulations.

EMERGENCY/FIRST AID PROCEDURES

Ingestion: Do not induce vomiting. Call poison control center. Call a physician immediately.

Eye Contact: Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician if eye irritation or blurry vision persists.

Skin Contact: Wash skin with mild soap and water. Call a physician if skin irritation or blurry vision persists. Launder affected clothing before re-wearing.

Inhalation: Remove to fresh air. Call a physician if irritation, nausea, dizziness, blurry vision or respiratory problems persist.

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements and is packaged in containers with at least 25% post-consumer recycled material.

The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Copyright © 2008 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, and StoneTech® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-20515 (08/08)



The miracles of science™