

# DuPont™ StoneTech® Professional Heavy Duty Exterior Sealer

## TECHNICAL DATA SHEET



### PRODUCT BENEFITS

- Heavy duty protection against water-based stains
- Weather resistant
- Minimizes efflorescence
- Preserves natural look
- Solvent-based formula
- Exterior use

### RECOMMENDED SURFACES

Natural stone such as granite, slate, tumbled stone and sandstone.

Masonry and concrete.

### AVAILABLE SIZES

Quart, Gallon, 5 Gallon, 55 Gallon

### COVERAGE

560–2,300 sq ft per gallon, depending on porosity of surface.

### EXPECTED WEAR

5–10 years.

### TECHNICAL INFORMATION

Form:	Liquid
Specific Gravity:	0.756
HMIS Rating:	2,2,0
Flash Point:	104°F

### VOC CONTENT

717 g/L

### DIRECTIONS

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, thoroughly dry and free of waxes and coatings. Surface temperature should be between 50°F and 80°F.

1. Mask any surfaces not intended to be treated.
2. Liberally apply an even coat with a paint pad, paintbrush, paint roller or low-pressure solvent-resistant sprayer. Do not thin before using.
3. Allow sealer to penetrate the surface for 5–15 minutes; denser material may require more time for sealer to penetrate. During this time, distribute excess sealer over entire area to ensure even penetration.
4. Thoroughly wipe the entire surface with a clean dry cloth to completely remove all excess sealer from the surface. DO NOT ALLOW EXCESS SEALER TO DRY ON THE SURFACE.
5. A second coat may be needed for porous, absorbent surfaces and should be applied one hour after initial application as directed in steps 2–4.
6. If sealer was not completely wiped off and a residue appears, wipe entire surface with a towel dampened with sealer. Use a white nylon pad to loosen residue and follow with a clean, white absorbent towel to remove.
7. Do not walk on surface for at least 4–6 hours. Full cure is achieved in 24–72 hours.
8. Clean up promptly after job is complete, since rags and equipment that are wet with product may be combustible. Clean equipment with mineral spirits and allow equipment and rags to dry in a well-ventilated area out of reach of children and pets. After rags are dry, dispose of in accordance with local waste disposal regulations.

### STORAGE AND HANDLING INSTRUCTIONS

**WARNING: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED.** Do not ingest. HARMFUL VAPORS. Avoid prolonged exposure to vapors. Use only in a well-ventilated area. For spray application, use a pump-up garden sprayer. DO NOT USE A POWER SPRAYER. Use a respirator if unsure that work area is well-ventilated. A NIOSH-approved respirator with a combination HEPA/organic vapor cartridge is recommended. Follow respirator manufacturer's instructions for use. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Avoid contact with eyes and skin. Wear solvent-resistant gloves such as nitrile gloves. KEEP OUT OF THE REACH OF CHILDREN. Do not store above 100°F/38°C. Do not mix with other chemicals.

### EMERGENCY/FIRST AID PROCEDURES

**Ingestion:** Do not induce vomiting. Call poison control center. Call a physician.

**Eye Contact:** Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician if eye irritation persists.

**Skin Contact:** Wash skin with mild soap and water. Call a physician if skin irritation persists. Launder affected clothing before re-wearing.

**Inhalation:** Remove to fresh air. Call a physician if irritation, nausea, dizziness or respiratory problems persist.

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements and is packaged in containers with at least 25% post-consumer recycled material.

PROTECT

CLEAN

TRANSFORM

DuPont StoneTech® Professional  
370 North Wiget Lane, Suite 200  
Walnut Creek, CA 94598

1-877-STONETECH (786-6383)

www.stonetechpro.dupont.com



The miracles of science™

*The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.*

*Copyright © 2008 DuPont. The DuPont Oval Logo, DuPont®, The miracles of science™, and StoneTech® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.*

K-20505 (08/08)