

DuPont™ StoneTech® Professional Salt Water Resistant Sealer

TECHNICAL DATA SHEET

PRODUCT BENEFITS

- High performance protection against salt water damage
- For natural stone and masonry surfaces around salt water pools
- Protects against water-based stains
- Preserves natural look
- Easy to use, water-based formula

RECOMMENDED SURFACES

Porous tile, natural stone, concrete pavers, terracotta, and grout. Best suited for porous substrates.

AVAILABLE SIZES

Gallon, 5 Gallon, 55 Gallon

COVERAGE

315–475 sq. ft. per gallon

EXPECTED WEAR

3–5 years on exterior surfaces.

TECHNICAL INFORMATION

Form:	Liquid
Specific Gravity:	0.98
HMIS Rating:	1,0,1
Flash Point:	NA
Freeze Point:	32°F
pH:	7–8

VOC CONTENT

<400 g/L (excluding water)

65 g/L (including water) (Low Solids Coating)

DIRECTIONS

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, dry and free of waxes and coatings. Surface temperature should be between 35°F and 90°F. Keep children and pets out of the area until foot traffic resumes.

1. Mask any surfaces not intended to be treated.
2. Liberally apply an even coat with a bristle paint brush or paint roller.
3. Allow sealer to penetrate the surface for 15–20 minutes. During this time, distribute excess sealer over entire area to ensure even penetration. Do not allow sealer to pool on the surface.
4. Thoroughly wipe the entire surface with a clean dry cloth to completely remove all excess sealer from the surface. **DO NOT ALLOW EXCESS SEALER TO DRY ON THE SURFACE.**
5. The sealer should be fully cured prior to water contacting the surface. Full cure is achieved in 72 hours. If there is a possibility of rain within the 72 hour cure time, cover surface so it remains dry.
6. Clean tools used during application with water.
7. If resistance to oily stains is also desired, apply DuPont™ StoneTech® Professional BulletProof® Sealer after Salt Water Resistant Sealer has fully cured.

STORAGE AND HANDLING INSTRUCTIONS

CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Do not spray. Avoid prolonged exposure to vapors. Use only in a well-ventilated area. Do not ingest. Avoid contact with eyes and skin. **KEEP OUT OF THE REACH OF CHILDREN.** Do not freeze or store above 100°F/38°C. Do not mix with other chemicals.

EMERGENCY/FIRST AID PROCEDURES

Ingestion: Do not induce vomiting. Call poison control center. Call a physician.

Eye Contact: Flush thoroughly with water for at least 15 minutes. Call a physician if eye irritation persists.

Skin Contact: Wash skin with mild soap and water. Call a physician if skin irritation persists. Launder affected clothing before re-wearing.

Inhalation: Remove to fresh air. Call a physician if respiratory irritation persists.

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements and is packaged in containers with at least 25% post-consumer recycled material.

PROTECT

CLEAN

TRANSFORM

DuPont StoneTech® Professional
370 North Wiget Lane, Suite 200
Walnut Creek, CA 94598

1-877-STONETECH (786-6383)

www.stonetechpro.dupont.com



The miracles of science™

The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Copyright © 2009 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, and StoneTech®, and BulletProof® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-22628 (6/09)