



# DuPont™ Universal Sealant

Style (identification): **1210S**

Language: **English**

## Product description & use:

DuPont™ Universal Sealant is a high-quality, durable, elastic polyurethane based adhesive sealant. DuPont™ Universal Sealant provides excellent adhesion to many surfaces and is extremely weatherproof, with long term durability against ageing. DuPont™ Universal Sealant is recommended for use with DuPont breather membranes (for roofs and walls), as well as DuPont VCL's and is suitable for both interior and exterior applications.

## Technical data:

- Colour: grey
- Density: 1.20 gr/cm<sup>3</sup>
- Cartridge capacity: 310 ml
- Cartridges per carton: 12
- Temperature resistance: -30 to +80°C (short time exposure to 100°C will not harm the sealant)
- Application temperature: +5 to +25°C
- Skin formation: approx. 2 hours (23°C and 50% rh)

## Processing tips & storage recommendations:

DuPont™ Universal Sealant adheres very efficiently to Tyvek® and many other materials, e.g. polyethylene, polypropylene, plastic, wood, metal, stone, etc.

- The base must be dry, frost-free, dust-free and grease-free.
- Apply a 5 to 6 mm wide bead of sealant evenly on the base.
- The cartridge should provide a continuous bead of approximately 13 - 16m.
- Contact between surfaces must be made within 10 minutes of the sealant application and pressed together lightly. The optimum thickness of the glue mass after pressing surfaces together should be approximately 2 mm.
- Glued joints should not be loaded mechanically during the first 3 to 6 hours (depending on the temperature and humidity).
- Cartridges may be stored at a temperature between 5°C and 25°C for up to 12 months in unopened original packaging, undercover and protected from direct sunlight.

**Issued on: 13.11.2008**

DuPont de Nemours (Luxembourg) S.à.r.l.  
L-2984 Luxembourg  
Tyvek® Marketing  
Fax: +352 3666 5021  
Tyvek® Customer Service  
Fax +352 3666 5018  
Tyvek® Manufacturing  
Fax +352 3666 5020  
E-mail: [tyvek.info@lux.dupont.com](mailto:tyvek.info@lux.dupont.com)

[www.construction.tyvek.com](http://www.construction.tyvek.com)

*This information corresponds to our current knowledge on the subject. It is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for any application other than the application as specified herein. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liabilities in connection with any use of this information for applications other than the application as specified herein. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. Product safety information is available on request. This data sheet is a printed document and is valid without signature.*

